

Series KD3x3

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD1040



KD1040 Standard

Art. No. 564000



KD1040 Premium

Art. No. 564001



AREAS OF APPLICATION

Technical Data

Type	KD1040-Standard		KD1040-Premium	
Voltage	3/PE/AC/50Hz/400V	10m HP-Hose DN08 - 315bar - Trigger-Gun with swivel - Spray-Lance 900mm c/w Vario-Nozzle - Stainless-Steel Jet-Nozzle 25° 17l Cleaning-Detergent tank - Detergent-Supply c/w Low-Pressure Injector and Metering-valve	- Hose-Reel 20m HP-Hose DN08 - 315bar - Trigger-Gun with swivel - Spray-Lance 900mm c/w Nozzle-Protection - Stainless-Steel Jet-Nozzle 25° - Spray-Lance 900mm c/w Rotary-Nozzle 15l Water-Storage tank - Water-Supply separation acc. DIN EN 1717 class 4 - Chemical supply in high-pressure Jet c/w Metering-valve	
Operating pressure	30-250bar/3-25MPa			
Max. pressure	270bar/27MPa			
Discharge capacity	300-1000l/h			
Nozzle size	045			
Max. Inlet temperature	45°C			
Pump speed	1400rpm			
Connected load	7,4kW/13,1A			
Electrical protection	3x16A slow			
Weight net/with package		89kg/113kg		97kg/121kg
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm		80,5x48,5x95cm/109x63x104cm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, ergonomic drawbar.

Art.No.	564000	564001
---------	--------	--------