

Series KD3x3

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD823 UK



KD823 UK Standard

Art. No. 562003



KD823 UK Premium

Art. No. 562004



AREAS OF APPLICATION

Technical Data

Type	KD823-UK Standard		KD823-UK Premium	
Voltage	1/N/PE/AC/50Hz/240V	10m HP-Hose DN08 - 315bar - Trigger-Gun with swivel - Spray-Lance 900mm c/w Vario-Nozzle - Stainless-Steel Jet-Nozzle 25° 17l Cleaning-Detergent tank - Detergent-Supply c/w Low-Pressure Injector and Metering-valve	- Hose-Reel 15m HP-Hose DN08 - 315bar - Trigger-Gun with swivel - Spray-Lance 900mm c/w Nozzle-Protection - Stainless-Steel Jet-Nozzle 25° - Spray-Lance 900mm c/w Rotary-Nozzle 15l Water-Storage tank - Water-Supply separation acc. DIN EN 1717 class 4 - Chemical supply in high-pressure Jet c/w Metering-valve	
Operating pressure	30-125bar/3-12,5MPa			
Max. pressure	155bar/15,5MPa			
Discharge capacity	300-720l/h			
Nozzle size	045			
Max. Inlet temperature	45°C			
Pump speed	1400rpm			
Connected load	3,1kW/12,3A			
Electrical protection	13A slow			
Weight net/with package		49kg/72kg	55kg/78kg	
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm	
Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar.				
Art.No.		562003	562004	